


Pendant Luminaires | 220-240 V | topLED 32 W | DALI | CRI 90  
8007N



| Technical data                                 |                     |
|--|---------------------|
| Installation position                          | Ceiling             |
| Installation environment                       | Indoor              |
| Light Source                                   | LED                 |
| Optics   | General Lighting    |
| Light emission direction                       | downward and upward |
| Power  | 32 W                |
| Luminous flux (source)                         | 4097 lm             |
| Frequency                                      | 50 - 60 Hz          |
| CCT / Tonalità                                 | 4000 K              |
| Colour rendering index                         | 90 Ra               |
| AC / DC  | AC                  |
| Safety class                                   | 1                   |
| IP   | IP20                |
| Optical compartment IP                         | IP40                |
| Glow wire test                                 | 650°                |
| Direct mounting on normally flammable surfaces | Yes                 |
| CE   | Yes                 |
| ETL  | No                  |
| Driver included                                | Yes                 |
| Dimmable article                               | DALI                |
| Induzione                                      | No                  |
| Emergency mode                                 | No                  |
| Motion sensor                                  | No                  |
| Directional                                    | No                  |
| Tilting  | No                  |
| Walk-over                                      | No                  |
| Drive-over                                     | No                  |
| Cable included                                 | No                  |
| Resin potting                                  | No                  |
| Net weight                                     | 3.950 Kg            |

| Finishing diffuser |         |
|--------------------|---------|
| Material           | PE      |
| Colour             | neutral |

| Finishing mounting frame |                         |
|--------------------------|-------------------------|
| Material                 | Aluminium               |
| Colour                   | embossed white RAL 9003 |
| Processing               | Coating                 |

Pendant Luminaires | 220-240 V | topLED 32 W | DALI | CRI 90  
**8007N**

Double emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 156 topled LEDs with CCT of 4000 K and a CRI 90; the source luminous flux is 4097 lm, with a 128.0 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The diffuser is made of pe; the mounting frame is made of aluminium, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 3.950 kg. The power supply driver is included in the delivery.

The total absorbed power is 32 W.

The device features protection class I and can be ceiling-mounted.

| Illuminotechnical Features            |                |
|---------------------------------------|----------------|
| Luminous flux (source)                | 4097 lm        |
| Colour temperature                    | 4000 K         |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Colour rendering index                | 90 Ra          |
| Life / Failure ratio                  | L80C0B20 80H   |