

# PRODUCT DATASHEET

## SST CLAS P 40 CL 5 W/2700 K E14

LED RELAX and ACTIVE CLASSIC P | LED lamps with two light colors in one lamp



---

### AREAS OF APPLICATION

- Wherever dimming was originally not planned
- Residential interiors
- Hospitality
- Outdoor applications only in suitable luminaires

---

### PRODUCT BENEFITS

- Easy dimming with double click of wall switch
- Easy and cost-effective operation, no dimmer required
- Low energy consumption
- Easy relamping thanks to compact design
- Instant 100 % light, no warm-up time
- Makes rooms multi-purpose with adjustable light atmosphere

---

### PRODUCT FEATURES

- Provides modes for 100 % and 30 % light output
- Controllable via standard wall switch
- Good quality of light; color rendering index  $R_a \geq 80$
- Mercury-free lamps



## TECHNICAL DATA


### Electrical data

Rated wattage	5.00 W
Nominal wattage	5.00 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz

### Photometrical data

Rated color temperature	2700 K
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	600 lm
Color rendering index Ra	≥80
Nominal luminous flux	600 lm

### Dimensions & weight



Overall length	78.0 mm
----------------	---------

### Temperatures & operating conditions

Maximum temperature at tc test point	50 °C
--------------------------------------	-------

### Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000

### Additional product data

Base (standard designation)	E14
-----------------------------	-----

<b>Mercury-free</b>	Yes
<b>Product remark</b>	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

## Capabilities

<b>Dimmable</b>	No
-----------------	----

## Certificates &amp; standards

<b>Energy efficiency class</b>	A++
--------------------------------	-----

## Country-specific categorizations

<b>Order reference</b>	LEDSCLP40ACT/RE
------------------------	-----------------

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075114340	SST CLAS P 40 CL 5 W/2700 K E14	Shipping carton box 6	285 mm x 153 mm x 136 mm	5.93 dm <sup>3</sup>	361.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.