

PRODUCT DATASHEET

ENDURA STYLE Cylinder Ceiling 6 W ST

ENDURA STYLE CYLINDER | Stainless steel wall-luminaires and bollards with indirect illumination



AREAS OF APPLICATION

- Outdoor use (IP44)
- Building facades
- Gardens, balconies and other outdoor areas
- Pathway lighting
- Driveways

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- Easy and quick installation

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Housing made of Polycarbonate covered with stainless steel
- Available as wall, ceiling and bollard luminaires



TECHNICAL DATA


Electrical data

Nominal wattage	6.00 W
Operating mode	Mains voltage
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Color rendering index Ra	>80
Light color (designation)	Warm White
Luminous flux	360 lm

Dimensions & weight



Diameter	102.0 mm
Height	87.0 mm
Product weight	270.00 g

Colors & materials

Body material	Stainless steel
Housing color	Steel
Product color	Steel
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...40 °C
---------------------------	-------------

Additional product data

Mounting type	Surface
---------------	---------

Mounting location	Wall
--------------------------	------

Capabilities

Dimmable	No
Type of connection	Screw terminal
LED module replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP44
Standards	CE/EAC/REACH/RoHS

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075205413	Folding carton box 1	124 mm x 154 mm x 166 mm	310.00 g	3.17 dm ³
4058075205420	Shipping carton box 6	380 mm x 175 mm x 320 mm	2091.00 g	21.28 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.